









OUT-BEAM UP/
FLOOD DOWN
WL

220-240V ~50/60Hz | 500mA
Systemleistung: 18W
Material: Aluminium / Glas

MANA OUT
WL, PHASE

220-240V ~50/60Hz | 500mA
Systemleistung: 11W
Material: Aluminium / Aluminium

SAIL
WL

200-240V ~50Hz
Systemleistung: 18W
Material: Aluminium



			A → G
Down	690lm 3000K		A → G F
Beam	50lm 3000K		A → G F

Variante	Art. Nr.
Down: 690lm 3000K CRI80 Beam: 50lm 3000K CRI80	
■ anthrazit	229665
Down: 690lm 3000K CRI80 Beam: 50lm 3000K CRI80	
■ grau	229664



			A → G
Up/Down	325lm 3000K		A → G E

Variante	Art. Nr.
Up: 325lm 3000K CRI80 Down: 325lm 3000K CRI80	
■ anthrazit	1002900
Up: 325lm 3000K CRI80 Down: 325lm 3000K CRI80	
■ rost	1002902



			A → G
1002605, 1002606	400lm 590lm 3000K		A → G F

Variante	Art. Nr.
400lm 3000K CRI80	
■ anthrazit	1002605
590lm 3000K CRI80	
□ weiß	1002606